

View Online at <https://aerobasegroup.com/nsn/6115-01-256-1059>

Prime Mover Cooling Medium:

Air

Mounting Type:

Skid shock tubular frame

Overall Length:

25.000 inches

Overall Height:

22.000 inches

Overall Width:

19.000 inches

Current Type:

Ac and dc

Direct Current Rating In Amps:

8.3

Dc Voltage Rating:

12.0 volts

Frequency Rating:

60.0 hertz

Accessory Component Quantity:

9

Accessory Controlling Agency:

T & j manufacturing

Winterization Feature:

Not included

Unpackaged Unit Weight:

180.000 pounds

Ac Wattage Rating:

3.1 kilowatts

Dc Wattage Rating:

100.0 watts

Line To Line Voltage In Volts:

120.0

Line To Neutral Voltage In Volts:

120.0 and 240.0

Power Factor In Percent:

100.0

Excitor Type:

Self-excited

Excitor:

Included

Prime Mover Starting Method:

Electric motor or manually by rope

Automatic Starting Feature:

Not provided

Prime Mover Manufacturer Name:

T & j manufacturing

Prime Mover Identifying Number:

30336r model no.

Housing Type:

Open

Accessory Component Name:

Pilot lamp; ac receptacle; dc receptacle; braker; fuse; change-over switch; key switch; oil alert; stop solenoid

Ambient Temperature In Deg Celsius:

20.0

Radio Interference Suppression:

Not included

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T322-a