

View Online at <https://aerobasegroup.com/nsn/6115-01-265-5045>

End Application:

Power plant, electric, 1500v

Special Features:

Prime mover cooling system, liquid; mounting type, trailer mounted; length 480inches max.; height 162 inch max.; width 96 inch max.; current type ac; frequency rating 60.0 hertz nom and 50.0 hertz nom; cooling method radiator; inclose type fully enclosed; winterization feature included; ac wattage rating 1500.0 kilowatts and 1350.0 kilowatts; line to line voltage in volts 4160.0 and 2400.0 and 3600.0 and 2100.0; line to neutral voltage in volts 2400.0 and 2100.0; exciter type self-excited; prime mover starting method electric start

Special Test Features:

Rated 4160v or 3600v line to line, 4 wire wye; rated 2400 vor 2100v line to line, 3 wire delta; can be remote controlled to 1000 feet away; iso container can ce removed from trailer

Supplementary Features:

Automatic mover starting method not provided; prime mover manufacturer caterpillar; housing type enclosed; ambient temp in degrees celsius -31.7 nd 51.7; temp rise rating in degrees 40.0; radio interference included; phase three and three

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A23800