

View Online at <https://aerobasegroup.com/nsn/6115-01-576-8942>

Mounting Type:

Tubular frame shock

Overall Length:

26.250 inches

Overall Height:

21.400 inches

Overall Width:

18.000 inches

Current Type:

Ac or dc

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

End Application:

Portable power

Inclosure Type:

Partially enclosed

Manufacturer Name:

Briggs and stratton

Ac Wattage Rating:

5500.0 watts and 6000.0 watts

Line To Line Voltage In Volts:

120.0 and 240.0

Housing Type:

Inclosed

Product Name:

Portable generator

Special Features:

Continuous current rating 45.8/22.9 amps; motor starting abili type 1.5hp; displacement/type 342cc/ohv; rated power at 3600rpm 11hp; starting system-recoil only; fuel tank 4.5 gallons; low oil protection; running time-full load 5.3 hours; run time-half load 8.5 hours

Supplementary Features:

120v receptacles straight blade (nema 5-20r) 4-20 amp; 120/140v receptacles twist-lock (nema l 14-30r) 1-30 amp; csa approved

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T322-a