NSN 6120-00-261-3671

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6120-00-261-3671 |
|--|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 11.000 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 9.250 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.562 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 6.5 kilovolt-ampere single component |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 14.375 inches |
| Body Width: |
| 10.875 inches |
| Body Height: |
| 12.688 inches |
| Inclosure Type: |
| Partially enclosed, half shell |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Cooling Method: |
| Self-cooled Self-cooled |
| Winding Function And Quantity: |
| 2 primary single component and 1 secondary single component |
| Winding Operating Voltage: |
| 396.00 ac volts single component 2nd primary and 420.00 ac volts single component 2nd primary and 440.00 ac volts single component |
| 2nd primary |
| Terminal Type And Quantity: |
| 10 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 6120-00-261-3671

Power Transformer - Page 2 of 2



Fiig:

A058b0