

View Online at <https://aerobasegroup.com/nsn/6120-01-469-9388>

**Reliability Indicator:**

Not established

**Mounting Hole Diameter:**

0.250 inches single group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Maximum Transformer Power Rating:**

150.0 volt-ampere single component

**Body Outside Diameter:**

3.900 inches

**Body Height:**

1.900 inches

**Maximum Operating Temp:**

65.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole single group

**Features Provided:**

Color coded lead and protective cover and special marking

**Winding Operating Current:**

0.7 amperes ac single component single primary and 1.4 amperes ac single component single primary

**Winding Operating Voltage:**

117.00 ac volts single component single secondary

**Special Features:**

Supply voltage range is plus or minus 10 percent; primaries are inside sleeve and must be connected together in series or parallel; primary lead wires are magnet wire self-leads, 24 gauge, 8.000 in. Length ; secondary lead wires are multi-stranded, 22 gauge, 8.000 in. Length ; core no. 900140, no-load loss equals 0.9 watt , no-load amperage equals 8.7 milliamps; ul recognized to ul 1411 and csa certified to csa c22.2, no. 66

**Terminal Type And Quantity:**

4 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0