

View Online at <https://aerobasegroup.com/nsn/6120-01-469-9388>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.250 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Maximum Transformer Power Rating:

150.0 volt-ampere single component

Body Outside Diameter:

3.900 inches

Body Height:

1.900 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole single group

Features Provided:

Color coded lead and protective cover and special marking

Winding Operating Current:

0.7 amperes ac single component single primary and 1.4 amperes ac single component single primary

Winding Operating Voltage:

117.00 ac volts single component single secondary

Special Features:

Supply voltage range is plus or minus 10 percent; primaries are inside sleeve and must be connected together in series or parallel; primary lead wires are magnet wire self-leads, 24 gauge, 8.000 in. Length ; secondary lead wires are multi-stranded, 22 gauge, 8.000 in. Length ; core no. 900140, no-load loss equals 0.9 watt , no-load amperage equals 8.7 milliamps; ul recognized to ul 1411 and csa certified to csa c22.2, no. 66

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0