## NSN 6125-00-028-6738

Motor-generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6125-00-028-6738

| Overall Height:  |
|--|
| 21.000 inches  |
| liilength:   |
| 38.750 inches  |
| Overall Width:   |
| 24.125 inches  |
| Current Type:  |
| Dc input   |
| Duty Cycle:  |
| Continuous   |
| Inclosure Feature:   |
| Dripproof-15 deg   |
| Mounting Method:   |
| Bed plate  |
| Mounting Facility Type And Quantity:   |
| 4 unthreaded hole  |
| Cooling Method:  |
| Self-ventilated Self-ventilated  |
| Inclosure Specificationification:  |
| Mil-std-108  |
| Bearing Type:  |
| Annular ball   |
| Features Provided:   |
| Horizontal mounting position   |
| Power Rating:  |
| 15000.0000 watts output  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:  |
| 20.000 inches  |
| Rotor Speed Rating In Rpm:   |
| 1800.0 single full load  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:   |
| 16.000 inches  |
| Connection Type And Voltage Rating In Volts:   |
| 230.0 konica, qh four-spline input   |
| Phase:   |
| Three output   |
| Frequency In Hertz:  |
| 60.0 output  |
| Test Data Document:  |
| 81349-mil-m-2130a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

1 type

**Specification Or Standard:** 

## NSN 6125-00-028-6738

Motor-generator - Page 2 of 2



| N/a               |  |
|-------------------|--|
| Unit Of Measure:  |  |
|                   |  |
| Demilitarization: |  |
| No                |  |
| Fiig:             |  |
|                   |  |

Mil-std (military Standard):

Mil-std-108 spec.

Shelf Life: