## NSN 6125-00-500-1036



Overall Height:         26.625 inches         lillength:         56.812 inches         Overall Width:         27.375 inches         Current Type:         Dc output         Duty Cycle:         Continuous         Inclosure Feature:         Dripproof-15 deg         Mounting Method:         Bed plate         Mounting Facility Type And Quantity:         8 unthreaded hole         Cooling Method:         Self-ventilated         Inclosure Specificationification:         Mil-std-108         Features Provided:         Horizontal mounting position         Power Rating:         10000.0000 watts output         Center To Center Distance Between Mounting Facilities Parallel To Length         23.750 inches         Tempurature Rating:         40.0 ambient degrees celsius         Rotor Speed Rating In Rpm:         180.0 single full load         Center To Center Distance Between Mounting Facilities Parallel To Width:         16.750 inches         Connection Type And Voltage Rating In Volts:         24.0.0 konica, qh four-spline input         Shelf Life:         N/a	View Onl	ine at https://aerobasegroup.com/nsn/6125-00-500-1036
liliength: 56.812 inches Overall Width: 27.375 inches Current Type: Dc output Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Overall F	leight:
A series of the	26.625 in	ches
Overall Width: 27.375 inches Current Type: Dc output Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	liilength:	
27.375 inches Current Type: Dc output Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	56.812 in	ches
Current Type: Dc output Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches	Overall V	Vidth:
De output Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 18.750 inches	27.375 in	ches
Duty Cycle: Continuous Inclosure Feature: Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches	Current <sup>-</sup>	Гуре:
Continuous Inclosure Feature: Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Dc outpu	t
Inclosure Feature: Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input	Duty Cyc	:le:
Dripproof-15 deg Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Continuo	us
Mounting Method: Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input	Inclosure	e Feature:
Bed plate Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Dripproof	-15 deg
Mounting Facility Type And Quantity: 8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Mounting	g Method:
8 unthreaded hole Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Bed plate	
Cooling Method: Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Mounting	g Facility Type And Quantity:
Self-ventilated Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	8 unthrea	ded hole
Inclosure Specificationification: Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Cooling	Method:
Mil-std-108 Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Self-venti	lated
Features Provided: Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Inclosure	e Specificationification:
Horizontal mounting position Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Mil-std-10	08
Power Rating: 10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Features	Provided:
10000.0000 watts output Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Horizonta	I mounting position
Center To Center Distance Between Mounting Facilities Parallel To Length 23.750 inches Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Power R	ating:
<ul> <li>23.750 inches</li> <li>Tempurature Rating:</li> <li>40.0 ambient degrees celsius</li> <li>Rotor Speed Rating In Rpm:</li> <li>1800.0 single full load</li> <li>Center To Center Distance Between Mounting Facilities Parallel To Width:</li> <li>16.750 inches</li> <li>Connection Type And Voltage Rating In Volts:</li> <li>240.0 konica, qh four-spline input</li> <li>Shelf Life:</li> </ul>	10000.00	00 watts output
Tempurature Rating: 40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Center T	o Center Distance Between Mounting Facilities Parallel To Length
40.0 ambient degrees celsius Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	23.750 in	ches
Rotor Speed Rating In Rpm: 1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Tempura	ture Rating:
1800.0 single full load Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	40.0 amb	ient degrees celsius
Center To Center Distance Between Mounting Facilities Parallel To Width: 16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Rotor Sp	eed Rating In Rpm:
16.750 inches Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	1800.0 si	ngle full load
Connection Type And Voltage Rating In Volts: 240.0 konica, qh four-spline input Shelf Life:	Center T	o Center Distance Between Mounting Facilities Parallel To Width:
240.0 konica, qh four-spline input Shelf Life:	16.750 in	ches
Shelf Life:	Connect	ion Type And Voltage Rating In Volts:
	240.0 kor	nica, qh four-spline input
N/a	Shelf Life	9:
	N/a	

Demilitarization:

No

Fiig:

A271a0

## NSN 6125-00-500-1036

Motor-generator - Page 2 of 2

## Mil-std (military Standard):

Mil-std-108 spec.

