## NSN 6125-00-846-7516

Motor-generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6125-00-846-7516

| Overall Height:   |  |  |  |  |
|---|--|--|--|--|
| 42.250 inches   |  |  |  |  |
| liilength:  |  |  |  |  |
| 62.625 inches   |  |  |  |  |
| Overall Width:  |  |  |  |  |
| 33.875 inches   |  |  |  |  |
| Current Type:   |  |  |  |  |
| Dc input  |  |  |  |  |
| Duty Cycle:   |  |  |  |  |
| Continuous  |  |  |  |  |
| Inclosure Feature:  |  |  |  |  |
| Dripproof-45 deg  |  |  |  |  |
| Mounting Method:  |  |  |  |  |
| Bed plate   |  |  |  |  |
| Mounting Facility Type And Quantity:  |  |  |  |  |
| 8 threaded hole   |  |  |  |  |
| Cooling Method:   |  |  |  |  |
| Self-ventilated   |  |  |  |  |
| Inclosure Specificationification:   |  |  |  |  |
| Mil-std-108   |  |  |  |  |
| Features Provided:  |  |  |  |  |
| Horizontal mounting position  |  |  |  |  |
| Frame Size Designation:   |  |  |  |  |
| 547 and 584   |  |  |  |  |
| Rotor Speed Rating In Rpm:  |  |  |  |  |
| 1714.0 single full load   |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                    |  |  |  |  |
| 37.000 inches   |  |  |  |  |
| Current Rating In Amps:   |  |  |  |  |
| 240.000 single output   |  |  |  |  |
| Connection Type And Voltage Rating In Volts:  |  |  |  |  |
| 250.0 line to neutral single input  |  |  |  |  |
| Phase:  |  |  |  |  |
| Three output  |  |  |  |  |
| Special Features:   |  |  |  |  |
| Two rows of four each mtg holes on 9.625 in. C to c, 11.625 in. C to c and 9.625 in. C to c |  |  |  |  |
| Frequency In Hertz:   |  |  |  |  |
| 400.0 output  |  |  |  |  |
| Terminal Type And Quantity:   |  |  |  |  |
| 6 solder lug  |  |  |  |  |
| Shelf Life:   |  |  |  |  |
| N/a   |  |  |  |  |

## NSN 6125-00-846-7516

Motor-generator - Page 2 of 2



| ι | Jnit  | Of | Measure:  |
|---|-------|----|-----------|
| • | ,,,,, | •  | moudai c. |

--

Demilitarization:

No

Fiig:

A271a0

Mil-std (military Standard):

Mil-std-108 spec.