Metallic Rectifier Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6130-00-067-8439

| Terminal Quantity:                                    |
|---|
| 7   |
| Terminal Type:  |
| Solder lug  |
| Overall Length:                                       |
| 3.875 inches  |
| Overall Diameter:                                     |
| 1.000 inches  |
| Mounting Configuration:                               |
| One 8-32 thd axial stud extending 3/8 in. On each end |
| Circuit Type:   |
| Bridge or doubler                                     |
| Rms Input Maximum Voltage Rating:                     |
| 26.0 volts and 52.0 volts                             |
| Load Type:  |
| Inductive or resistive                                |
| Mounting Method:                                      |
| Stud  |
| Operating Ambient Tempurature Range:                  |
| +0.0 to 50.0 degrees celsius                          |
| Rectifying Material:                                  |
| Selenium  |
| Individual Circuit Connection Quantity:               |
| 2   |
| Rectification Method:                                 |
| Full wave and half wave                               |
| Maximum Output Current Rating:                        |
| 150.0 milliamperes and 75.0 milliamperes              |
| Dc Output Maximum Voltage Rating:                     |
| 21.0 volts new  |
| Phase:  |
| Single  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |
|   |
| Demilitarization:                                     |
| No  |
| Fiig:   |
| T320-I  |
|   |