NSN 6130-00-264-6044

Metallic Rectifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-264-6044

| Terminal Quantity: |
|-------------------------------------------------------------------------|
| 3 |
| Terminal Type: |
| Solder lug |
| Tempurature Rating: |
| 50.0 degrees celsius |
| Overall Height: |
| 1.000 inches |
| Overall Width: |
| 1.000 inches |
| Mounting Method: |
| Holes |
| Environmental Protection: |
| Moisture |
| Circuit Connection Style Designator: |
| Center tap 1 phase |
| Mounting Configuration: |
| Four 3/16 in. Diameter mtg holes on 5-5/16 in. By 19/32 in. Mtg centers |
| Inclosure Feature: |
| Unenclosed |
| Rms Input Maximum Voltage Rating: |
| 320.0 volts |
| Dc Output Maximum Current Rating: |
| 100.000 milliamperes |
| Load Type: |
| Inductive |
| Dc Output Maximum Voltage Rating: |
| 100.0 volts new |
| Stack Quantity: |
| 1 |
| Grounded Terminal: |
| Not included |
| Stacklength: |
| 4.875 inches |
| Material: |
| Selenium |
| Material: |
| Selenium |
| Shelf Life: |
| N/a |
| 14/4 |

--

NSN 6130-00-264-6044Metallic Rectifier - Page 2 of 2



Demilitarization:

No

Fiig:

T327-b