NSN 6130-00-284-0223

Metallic Rectifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-284-0223

Terminal Quantity:
5
Terminal Type:
Solder lug
Tempurature Rating:
50.0 degrees celsius
Overall Height:
2.625 inches
Overall Width:
2.625 inches
Mounting Method:
Bracket
Environmental Protection:
Moisture and salt spray resistant
End Application:
Model no. 34e72-2
Circuit Connection Style Designator:
Bridge 3 phase
Mounting Configuration:
Four 0.218 in. By 0.375 in. Mtg slots on 10-15/32 in. By 1.875 in. Mtg centers
Inclosure Feature:
Unenclosed
Unenclosed
Unenclosed Rms Input Maximum Voltage Rating:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new Stack Quantity:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new Stack Quantity:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new Stack Quantity: 1 Grounded Terminal:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new Stack Quantity: 1 Grounded Terminal: Not included
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new Stack Quantity: 1 Grounded Terminal: Not included Stacklength:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new Stack Quantity: 1 Grounded Terminal: Not included Stacklength: 11.900 inches
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new Stack Quantity: 1 Grounded Terminal: Not included Stacklength: 11.900 inches Material:
Unenclosed Rms Input Maximum Voltage Rating: 156.0 volts Dc Output Maximum Current Rating: 3.600 amperes Load Type: Resistive Dc Output Maximum Voltage Rating: 178.0 volts new Stack Quantity: 1 Grounded Terminal: Not included Stacklength: 11.900 inches Material: Selenium

N/a

NSN 6130-00-284-0223

Metallic Rectifier - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

T327-b