## NSN 6130-00-295-2294

Metallic Rectifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-295-2294

Terminal Quantity:
4
Terminal Type:
Solder lug
Overall Length:
1.953 inches
Tempurature Rating:
35.0 degrees celsius
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Mounting Method:
Stud
Environmental Protection:
Moisture
End Application:
Type an/mrn-9
Circuit Connection Style Designator:
Bridge 1 phase
Mounting Configuration:
Two no. 0.22 thd mtg stude legated and an each and
Two no. 8-32 thd mtg studs located one on each end
Rms Input Maximum Voltage Rating:
•
Rms Input Maximum Voltage Rating:
Rms Input Maximum Voltage Rating: 26.0 volts
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating:
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type:
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type: Inductive and resistive
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type: Inductive and resistive  Dc Output Maximum Voltage Rating:
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes Load Type: Inductive and resistive Dc Output Maximum Voltage Rating: 18.0 volts new
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type: Inductive and resistive  Dc Output Maximum Voltage Rating: 18.0 volts new  Stack Quantity:
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type: Inductive and resistive  Dc Output Maximum Voltage Rating: 18.0 volts new  Stack Quantity: 1
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes Load Type: Inductive and resistive Dc Output Maximum Voltage Rating: 18.0 volts new Stack Quantity: 1 Grounded Terminal:
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type: Inductive and resistive  Dc Output Maximum Voltage Rating: 18.0 volts new  Stack Quantity: 1  Grounded Terminal: Not included
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type: Inductive and resistive  Dc Output Maximum Voltage Rating: 18.0 volts new  Stack Quantity: 1  Grounded Terminal: Not included  Material:
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type: Inductive and resistive  Dc Output Maximum Voltage Rating: 18.0 volts new  Stack Quantity: 1  Grounded Terminal: Not included  Material: Selenium
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes  Load Type: Inductive and resistive  Dc Output Maximum Voltage Rating: 18.0 volts new  Stack Quantity: 1  Grounded Terminal: Not included  Material: Selenium  Material:
Rms Input Maximum Voltage Rating: 26.0 volts  Dc Output Maximum Current Rating: 150.000 milliamperes Load Type: Inductive and resistive  Dc Output Maximum Voltage Rating: 18.0 volts new  Stack Quantity: 1  Grounded Terminal: Not included  Material: Selenium  Material: Selenium

--

## NSN 6130-00-295-2294

Metallic Rectifier - Page 2 of 2



Demilitarization:

No

Fiig:

T327-b