NSN 6130-00-435-5212

Power Supply - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-435-5212

Overall Length:
4.670 inches
Overall Height:
3.400 inches
Overall Width:
3.280 inches
Environmental Protection:
Hermetically sealed
Electrical Power Source Relationship:
Operating
Input Phase:
Single single operating power rqmt
Input Voltage Rating:
105.0 ac volts single operating power rqmt and 125.0 ac volts single operating power rqmt
Output Voltage Rating:
35.0 dc volts single power output
Input Frequency Rating:
50.0 hertz single operating power rqmt and 400.0 hertz single operating power rqmt
Operating Ambient Tempurature Range:
-10.0/+65.0 degrees celsius
Output Control Quantity:
1 single power output
Output Control Type:
Voltage adjustment single power output
Rectification Method:
Rectification Method: Single phase full wave bridge
Single phase full wave bridge
Single phase full wave bridge Features Provided:
Single phase full wave bridge Features Provided: Filter
Single phase full wave bridge Features Provided: Filter Output Current Rating:
Single phase full wave bridge Features Provided: Filter Output Current Rating: 200.0 dc milliamperes single power output
Single phase full wave bridge Features Provided: Filter Output Current Rating: 200.0 dc milliamperes single power output Ripple Voltage At Full Load:
Single phase full wave bridge Features Provided: Filter Output Current Rating: 200.0 dc milliamperes single power output Ripple Voltage At Full Load: 1.0 millivolts rms single power output
Single phase full wave bridge Features Provided: Filter Output Current Rating: 200.0 dc milliamperes single power output Ripple Voltage At Full Load: 1.0 millivolts rms single power output Output Control Location:
Single phase full wave bridge Features Provided: Filter Output Current Rating: 200.0 dc milliamperes single power output Ripple Voltage At Full Load: 1.0 millivolts rms single power output Output Control Location: Front panel single power output
Single phase full wave bridge Features Provided: Filter Output Current Rating: 200.0 dc milliamperes single power output Ripple Voltage At Full Load: 1.0 millivolts rms single power output Output Control Location: Front panel single power output Output Connection Quantity:
Single phase full wave bridge Features Provided: Filter Output Current Rating: 200.0 dc milliamperes single power output Ripple Voltage At Full Load: 1.0 millivolts rms single power output Output Control Location: Front panel single power output Output Connection Quantity: 2 single power output
Single phase full wave bridge Features Provided: Filter Output Current Rating: 200.0 dc milliamperes single power output Ripple Voltage At Full Load: 1.0 millivolts rms single power output Output Control Location: Front panel single power output Output Connection Quantity: 2 single power output Output Connection Type:

Input Connection Quantity:

2 single operating power rqmt

NSN 6130-00-435-5212

Power Supply - Page 2 of 2



Ventilation Design Type:
A mala in a mala min
Ambient air
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A39900