NSN 6130-00-519-1044

Metallic Rectifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-519-1044

Terminal Quantity:

Terminal Quantity:
4
Terminal Type:
Solder lug
Overall Length:
3.766 inches
Tempurature Rating:
-35.0 degrees celsius and 75.0 degrees celsius
Overall Height:
3.210 inches
Overall Width:
3.370 inches
Mounting Method:
Bolt
Environmental Protection:
Fungus and moisture
Circuit Connection Style Designator:
Bridge 1 phase
Mounting Configuration:
One 5/16-18 thd bolt centrally located at one end
Rms Input Maximum Voltage Rating:
Rms Input Maximum Voltage Rating: 60.4 volts
60.4 volts
60.4 volts Dc Output Maximum Current Rating:
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type:
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating:
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity:
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity:
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity: 4 Grounded Terminal:
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity: 4 Grounded Terminal: Not included
Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity: 4 Grounded Terminal: Not included Material:
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity: 4 Grounded Terminal: Not included Material: Selenium
Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity: 4 Grounded Terminal: Not included Material: Selenium Material:
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity: 4 Grounded Terminal: Not included Material: Selenium Material: Selenium
60.4 volts Dc Output Maximum Current Rating: 3.000 milliamperes Load Type: Resistive Dc Output Maximum Voltage Rating: 48.0 volts new Stack Quantity: 4 Grounded Terminal: Not included Material: Selenium Material: Selenium Shelf Life:

No

Demilitarization:

NSN 6130-00-519-1044Metallic Rectifier - Page 2 of 2



Fiig:

T327-b