Metallic Rectifier Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6130-00-557-8949

Terminal C	uantity:
9	
Terminal T	ype:
Solder lug	
Overall Le	ngth:
12.563 inch	es
Overall He	ght:
3.313 inche	S
Overall Wi	dth:
3.000 inche	S
Grounding	Provision:
Not include	d
Mounting	Configuration:
Eight 3/8 in	. By 7/16 in. Mtg slots arranged into 2 rows of 4 slots ea, slots in ea row spaced 4-7/16 in., 2-7/8 and 4-7/16 in. C to c
respectively	ν, rows spaced 1 in. C to c
Circuit Typ	e:
Doubler	
Rms Input	Maximum Voltage Rating:
165.0 volts	
Load Type	
Resistive	
Mounting I	Nethod:
Bracket	
Operating	Ambient Tempurature Range:
+0.0/+50.0	degrees celsius
Rectifying	Material:
Selenium	
Individual	Circuit Connection Quantity:
3	
Rectification	on Method:
Full wave a	nd half wave
Maximum	Output Current Rating:
1.8 ampere	S
Phase:	
Single	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	
Fiig:	
T320-I	