NSN 6130-00-635-8083

Metallic Rectifier - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-635-8083

| Terminal Quantity: |
|--|
| 4 |
| Terminal Type: |
| Solder lug |
| Overall Length: |
| Between 4.594 inches and 4.656 inches |
| Tempurature Rating: |
| 35.0 degrees celsius |
| Overall Diameter: |
| Between 2.157 inches and 2.219 inches |
| Mounting Method: |
| Stud |
| Environmental Protection: |
| Moisture |
| End Application: |
| Type no. Ab-221/tps-10 |
| Circuit Connection Style Designator: |
| Bridge 1 phase |
| Mounting Configuration: |
| Mount by two no. 0.250 in20 thd nc-2 studs 0.500 in. Lg mtg studs, one located on each end |
| Rms Input Maximum Voltage Rating: |
| 121.0 volts |
| Dc Output Maximum Current Rating: |
| 1.100 amperes |
| Load Type: |
| Resistive |
| Dc Output Maximum Voltage Rating: |
| 96.0 volts new |
| Stack Quantity: |
| 1 |
| Grounded Terminal: |
| Not included |
| Material: |
| Selenium |
| Material: |
| Selenium |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 6130-00-635-8083 Metallic Rectifier - Page 2 of 2



Fiig:

T327-b