## NSN 6130-00-674-0683

Metallic Rectifier Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-674-0683

Terminal Quantity:
9
Terminal Type:
Solder lug
Overall Length:
3.687 inches
Overall Height:
1.220 inches
Overall Width:
1.000 inches
Grounding Provision:
Not included
Mounting Configuration:
No. 8 (0.164) in 32 thd axial mtg stud extending 0.691 in. From bridge end of rectifier
Circuit Type:
Center tap or bridge or half wave
Rms Input Maximum Voltage Rating:
26.0 volts and 52.0 volts
Load Type:
Resistive or resistive
Mounting Method:
Stud
Operating Ambient Tempurature Range:
-54.0 to 71.0 degrees celsius and -54.0 to 71.0 degrees celsius and -54.0 to 71.0 degrees celsius
Rectifying Material:
Selenium
Individual Circuit Connection Quantity:
1 and 2 and 1
Rectification Method:
Full wave and full wave and half wave
Maximum Output Current Rating:
250.0 milliamperes and 250.0 milliamperes and 125.0 milliamperes
Dc Output Maximum Voltage Rating:
18.0 volts new and 10.0 volts aged
Phase:
Single or single
Surface Treatment:
Moisture resistant
Surface Treatment:
Moisture resistant
Shelf Life:

N/a

## NSN 6130-00-674-0683 Metallic Rectifier Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

T320-I