Metallic Rectifier Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-803-1917

Termi	nal Quantity:
6	
Termi	nal Type:
Solder	lug
Overa	II Length:
5.781	inches
Overa	II Height:
3.125	inches
Overa	ll Width:
3.125	inches
Grour	nding Provision:
Not in	cluded
Moun	ting Configuration:
Four 0	0.218 in. By 3/8 in. Slots on 1-7/8 in. By 6-17/32 in. Mtg centers
Circui	t Туре:
-	or half wave
Rms I	nput Maximum Voltage Rating:
66.0 v	olts and 264.0 volts
Load	Туре:
Resist	
Moun	ting Method:
Brack	
-	ting Ambient Tempurature Range:
	30.0 degrees celsius
Rectif	ying Material:
Seleni	
	dual Circuit Connection Quantity:
2	
	ication Method:
	ave and half wave
	num Output Current Rating:
	nperes and 3.7 amperes
	Itput Maximum Voltage Rating:
	olts new and 109.1 volts new
Phase	
Single	
Shelf	Life:
N/a	
Unit C	of Measure:
	itarization:
No	

NSN 6130-00-803-1917 Metallic Rectifier Assembly - Page 2 of 2

Fiig: T320-I

