Metallic Rectifier Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-00-823-2296

| Terminal Quantity: |
|--|
| 4 |
| Terminal Type: |
| Screw |
| Overall Length: |
| 9.875 inches |
| Overall Height: |
| 2.313 inches |
| Overall Width: |
| 2.813 inches |
| Grounding Provision: |
| Not included |
| Mounting Configuration: |
| Four mtg slots 3/16 in. W spaced on 1-1/2 in. By 9-3/8 in. Centers |
| Circuit Type: |
| Half wave |
| Rms Input Maximum Voltage Rating: |
| 264.0 volts |
| Load Type: |
| Resistive |
| Mounting Method: |
| Bracket |
| Operating Ambient Tempurature Range: |
| +0.0/+40.0 degrees celsius |
| Rectifying Material: |
| Selenium |
| Individual Circuit Connection Quantity: |
| 2 |
| Rectification Method: |
| Half wave |
| Maximum Output Current Rating: |
| 650.0 milliamperes |
| Dc Output Maximum Voltage Rating: |
| 18.0 volts new |
| Phase: |
| Single |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 6130-00-823-2296

Metallic Rectifier Assembly - Page 2 of 2

Fiig: T320-I

