

View Online at <https://aerobasegroup.com/nsn/6130-01-122-0308>

**Environmental Protection:**

Moisture proof

**End Application:**

Emk9mod2, module, 8-cell system, ffh01 class; mk9mod2, 8-cell system, ffh01, eqty cmpt; mk4mod3, sequencer, launch, ffh01 class; mk4mod3, sequencer, launch, ffh01 cl, eqty cmpt; mk9mod0, module, 8-cell system, ffh01 class; mk9mod0, module, 8-cell system, ffh01 cl, eqty cmpt; mk10mod0, module, 8-cell, f246 class; mk11mod0, module, 8-cell system, f246 class; mk10mod0, module, 8-cell, f246 class cosmal; mk11mod0, module, 8-cell system, f246 class cosmal

**Document Source:**

10001

**Maximum Operating Altitude Rating:**

10000.0 feet

**Operating Ambient Temperature Range:**

-46.0/+80.0 degrees celsius

**Product Name:**

Inavy: power supply; drawing name: power supply, d.C. (10-600 v variable)

**Special Features:**

Life expectancy 10 years; shock and vibration resistant; meets airborne and structureborne noise requirements of mil-std-740 for grade b, type 3 equipment; weight is 3.5 lbs ; meets electrical and electromagnetic compatibility requirements; depot repairable; additional information found when using cage code 10001 while retrieving drawing documentation through jedmics

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A39900