

View Online at <https://aerobasegroup.com/nsn/6130-01-134-4748>

Overall Length:

4.875 inches

Overall Height:

1.750 inches

Overall Width:

4.000 inches

End Application:

Multi-purpose

Electrical Power Source Relationship:

Operating

Input Phase:

Three single operating power rqmt

Input Voltage Rating:

100.0 ac pounds per hour dry single operating power rqmt and 240.0 ac pounds per hour with retaining chain single operating power rqmt

Output Voltage Rating:

24.0 dc volts single power output

Input Frequency Rating:

47.0 hertz single operating power rqmt and 63.0 hertz single operating power rqmt

Operating Ambient Temperature Range:

+0.1/+70.0 degrees celsius

Output Wattage Rating:

28.0 watts single power output

Output Current Rating:

1.2 dc amperes single power output

Output Phase:

Single single power output

Ripple Voltage At Full Load:

13.5 millivolts average single power output

Output Connection Quantity:

2 single power output

Output Connection Type:

Solder stud single power output

Input Connection Type:

Solder lug single operating power rqmt

Input Connection Quantity:

5 single operating power rqmt

Special Features:

Remote sensing, internal strapping fpr input voltage, per mil-std-810c, method 514, procedure x, shock per mil-std-810c, method 516, procedure v, automatic current limit/ foldback, output ripple .02% pk-pk max, line regulation +/- .05% for a 10% line change, load regulation +/- .05% for a 50% load change, efficiency 60%, stability +/- .03% for 24 hr period after 1 hr warm up

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A39900