NSN 6130-01-142-0120

Power Supply - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6130-01-142-0120

Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Input Frequency Rating: 50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt. Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fing:	
Overall Height: 4.940 inches Overall Width: 7.500 inches Electrical Power Source Relationship: Operating Input Phase: Single single operating power repmt Input Voltage Rating: 105.0 a c pounds per hour dry single operating power repmt and 132.0 a c pounds per hour with relating chain single operating power repmt Output Voltage Rating: 105.0 ac pounds per hour dry single operating power output 105.0 ac pounds per hour dry single operating power output 105.0 ac pounds per hour dry single operating power output 105.0 ac pounds per hour dry single operating power output 105.0 ac pounds per hour dry single operating power output 105.0 ac pounds per hour dry single operating power output 105.0 ac pounds per hour dry single operating power output 105.0 ac pounds per hour dry single operating power output 105.0 ac pounds per hour dry single operating power output 10.1 Ar Tot.0 degrees celsius Fatures Provided: 10.1 degrees single power output and 100.0 dc amperes single power output 10.1 dc amperes single power output and 100.0 dc amperes single power output 10.1 dc Amperes: 10.1 dc Amperes: 10.1 dC Measure: <td>-</td>	-
A 940 index Verall Width: 7.500 inches Electrical Power Source Relationship: Operating Input Phase: Single single operating power rqmt Input Voltage Rating: 105.0 ac pounds per hour dy single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt 105.0 ac pounds per hour dy single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt and 40.0 hertz single operating power rqmt and 40.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt 4.5 d volts single operating power rqmt and 440.0 hertz single operating power rqmt 5.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt 4.5 d volts resperative Range: 4.5 d volt 4.7 1.0 degrees celsius Fliter Fliter 1.6 duit degrees celsius Fliter 1.6 duit degrees celsius 1.6 duit degrees celsius 1.7 duit degrees celsius 1.8 duit degrees celsius	14.000 inches
Overall Width: 7.500 inches Electrical Power Source Relationship: Operating Iput Phase: Single single operating power reprit Ingut Voltage Rating: 105.0 ac pounds per hour dry single operating power reprit and 132.0 ac pounds per hour with retaining chain single operating power reprit and 132.0 ac pounds per hour with retaining chain single operating power reprit and 132.0 ac pounds per hour with retaining chain single operating power reprit voltage Rating: 105.0 ac pounds per hour dry single operating power output Hourt Forquency Rating: 45.d volts single operating power reprit and 440.0 hertz single operating power reprit Portaring Ambient Tempurature Range: 40.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 1040 da camperes single power output and 100.0 da camperes single power output Na Lind Cleasure: 11. Na Lind Measure: 12. Na Lind Cleasure: 12. 13. 14. 14. 15. 16. 16. 17. <	Overall Height:
7.500 inches Electrical Power Source Relationship: Operating Iput Phase: Single single operating power romt Input Voltage Rating: 105.0 ac pounds per hour dry single operating power romt and 132.0 ac pounds per hour with retaining chain single operating power romt and 132.0 ac pounds per hour single operating power romt and 132.0 ac pounds per hour single operating power romt and 132.0 ac pounds per hour single operating power romt and 132.0 ac pounds per hour single operating power romt Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Piput Frequency Rating: 6.0 hertz single operating power romt and 440.0 hertz single operating power romt Pourating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shell Life: Na Int Of Measure: Pomilitarization: No Fig:	4.940 inches
Electrical Power Source Relationship: Operating Iput Phase: Single single operating power rqmt Iput Voltage Rating: 105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Iput Frequency Rating: 50.0 hetrz single operating power rqmt and 440.0 hertz single operating power rqmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shell Life: Na Int of Measure: Filter Int of Measure: Pointiliarization: No Filter Int of Measure:	Overall Width:
Operating Input Phase: Single single operating power rgmt Input Voltage Rating: 105.0 ac pounds per hour dry single operating power rgmt and 132.0 ac pounds per hour with retaining chain single operating power rgmt Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Input Frequency Rating: 50.0 hertz single operating power rgmt and 440.0 hertz single operating power rgmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: Na Init of Measure: - - Finalitarization: No Fig:	7.500 inches
Input Phase: Single single operating power rqmt Input Voltage Rating: 105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Input Frequency Rating: 50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Electrical Power Source Relationship:
Input Voltage Rating: 105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Input Frequency Rating: 50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 4.0.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: - Pomilitarization: No Fig:	Operating
Input Voltage Rating: 105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Input Frequency Rating: 50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Init of Measure: - Demiltarization: No Fig:	Input Phase:
105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Input Frequency Rating: 50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit of Measure: - Demilitarization: No Fig:	Single single operating power rqmt
Output Voltage Rating: 4.5 dc volts single power output and 6.0 dc volts single power output Input Frequency Rating: 50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt. Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: - Pomilitarization: No Fig:	Input Voltage Rating:
4.5 dc volts single power output and 6.0 dc volts single power output Input Frequency Rating: 50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Dint Of Measure: - Demilitarization: No Fig:	105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt
Input Frequency Rating: 50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Fig:	Output Voltage Rating:
50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	4.5 dc volts single power output and 6.0 dc volts single power output
Operating Ambient Tempurature Range: +0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Input Frequency Rating:
+0.1/+71.0 degrees celsius Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output 40.0 dc amperes single power output and 100.0 dc amperes single power output 5helf Life: N/a Unit Of Measure: Demilitarization: No Filg:	50.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt
Features Provided: Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Operating Ambient Tempurature Range:
Filter Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	+0.1/+71.0 degrees celsius
Output Current Rating: 40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Features Provided:
40.0 dc amperes single power output and 100.0 dc amperes single power output Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Filter
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Output Current Rating:
N/a Unit Of Measure: Demilitarization: No Fiig:	40.0 dc amperes single power output and 100.0 dc amperes single power output
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A 39900	Fiig:
	A39900