NSN 6130-01-225-7031

Power Supply - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-01-225-7031

Overall Length:
7.047 inches
Overall Height:
3.172 inches
Overall Width:
3.719 inches
Environmental Protection:
Fungus proof
Document Source:
80103
Electrical Power Source Relationship:
Operating
Installation Design:
Rack
Input Phase:
Single single operating power rqmt
Frequency Regulation Percent:
0.01 single power output
Input Voltage Rating:
105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqmt
Output Voltage Rating:
28.0 dc volts single power output
Input Frequency Rating:
47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt
Operating Ambient Tempurature Range:
-20.0/+71.0 degrees celsius
Output Control Quantity:
1 single power output
Output Control Type:
Voltage adjustment single power output
Features Provided:
Circuit overload protection device and over current protector and potentiometer
Criticality Code Justification:
Feat
Output Current Rating:
0.6 dc amperes single power output and 1.0 dc amperes single power output
Power Supply Output Current/voltage Characteristics:
Limiting current single power output
Ripple Voltage At Full Load:

Output Control Location:

Front panel single power output

250.0 microvolts rms single power output

NSN 6130-01-225-7031

Power Supply - Page 2 of 2



Output Connection Quantity:
2 single power output
Output Connection Type:
Solder lug single power output
Input Connection Type:
Solder lug single operating power rqmt
Input Connection Quantity:
2 single operating power rqmt
Ventilation Design Type:
Convection
Special Features:
Barrier strip added to rear deck
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A39900