

View Online at <https://aerobasegroup.com/nsn/6130-01-328-2159>

**End Application:**

Module readout cam mk ii

**Electrical Power Source Relationship:**

Operating

**Input Phase:**

Single single operating power rqmt

**Frequency Regulation Percent:**

4.0 single power output

**Input Voltage Rating:**

115.0 ac volts single operating power rqmt

**Output Voltage Rating:**

18.0 dc pounds per hour wet single power output

**Input Frequency Rating:**

60.0 hertz single operating power rqmt

**Operating Ambient Temperature Range:**

+10.0/+70.0 degrees celsius

**Features Provided:**

Over temperature protection and over current protector and over voltage protector

**Output Current Rating:**

10.0 dc amperes single power output

**Ripple Voltage At Full Load:**

100.0 millivolts peak single power output

**Output Connection Quantity:**

1 single power output

**Output Connection Type:**

Connector, receptacle single power output

**Input Connection Type:**

Connector, receptacle single operating power rqmt

**Input Connection Quantity:**

1 single operating power rqmt

**Reference Number Differentiating Characteristics:**

Selected tested and certified for trident submarine application

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A39900