## NSN 6130-01-329-7415

Power Supply Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-01-329-7415 **Overall Length:** 23.500 inches **Overall Height:** 5.250 inches Overall Width: 19.000 inches **End Application:** An/fps/120; next assembly g245070-1 or g452071-1; used on bmews **Maximum Operating Altitude Rating:** 10000.0 feet **Electrical Power Source Relationship:** Operating **Power Unit Type:** Silicon controlled rectifier single operating power rqmt Installation Design: Rack Input Phase: Single single operating power rqmt **Input Voltage Rating:** 115.0 ac pounds per hour wet single operating power rqmt **Output Voltage Rating:** 4.75 dc volts 3rd power output and 5.25 dc volts 3rd power output **Input Frequency Rating:** 60.0 hertz single operating power rqmt **Operating Ambient Tempurature Range:** -0.0/+40.0 degrees celsius **Power Unit Quantity: Features Provided:** On-off switch-indicator and over voltage protector and voltage adjustment **Output Current Rating:** 9.5 dc amperes 2nd power output Ripple Voltage At Full Load: 150.0 microvolts average multiple power outputs w/identical ratings **Output Connection Quantity:** 5 single power output **Output Connection Type:** Connector, receptacle single power output **Input Connection Type:** Connector, plug single operating power rqmt

**Input Connection Quantity:** 

1 single operating power rqmt

## NSN 6130-01-329-7415

Power Supply Assembly - Page 2 of 2



۷	enti	lation	Desig	n Type:

Air cooled

## **Special Features:**

Altered item from cage 49956 p/n g452142-1; vendor item lambda cage 80103 assembly number 23571-1; consisting of power supply p/n lds-p-20 q type 2; p/nlds-p-5-ov-40100-1 q type 1; p/n l-20-ov-20 qty2; p/n lra-17 q type 1; lm-ov-1 qty1; added undervoltage detection circuitrywhich creates a margined output

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A39900