Power Supply - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-01-344-8395

Overall Length:

7.203 inches

Overall Height:

1.687 inches

Overall Width:

4.531 inches

Environmental Protection:

Fungus proof

End Application:

Fscn/cue

Electrical Power Source Relationship:

Operating

Input Phase:

Single single operating power rqmt

Input Voltage Rating:

187.0 ac pounds per hour dry 1st alternate operating power rqmt and 265.0 ac pounds per hour with retaining chain 1st alternate operating power rqmt95.0 ac pounds per hour dry 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain 2nd alternate operating power rqmt and 132.0 ac pounds per hour with retaining chain

Output Voltage Rating:

14.25 dc volts single power output and 15.75 dc volts single power output

Input Frequency Rating:

47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt

Operating Ambient Tempurature Range:

-10.0/+71.0 degrees celsius

Features Provided:

Circuit overload protection device and fuse and emi filter and remote error sensing capability and over voltage protector

Output Current Rating:

2.1 dc amperes single power output and 4.2 dc amperes single power output

Output Connection Quantity:

2 single power output

Output Connection Type:

Screw single power output

Input Connection Type:

Terminal strip single operating power rqmt

Input Connection Quantity:

2 single operating power rqmt

Ventilation Design Type:

Convection

Power Supply Efficiency Line:

77.0

Shelf Life:

N/a

Unit Of Measure:

NSN 6130-01-344-8395

Power Supply - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A39900

