NSN 6130-01-364-7183

Power Supply - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/6130-01-364-7163
Overall Length:
9.010 inches
Overall Height:
1.880 inches
Overall Width:
6.090 inches
End Application:
Short range radar
Electrical Power Source Relationship:
Operating
Input Phase:
Single 1st alternate operating power rqmtsingle 2nd alternate operating power rqmt
Input Voltage Rating:
100.0 ac pounds per hour dry 1st alternate operating power rqmt and 135.0 ac pounds per hour with retaining chain 1st alternate operating
power rqmt200.0 ac pounds per hour dry 2nd alternate operating power rqmt and 270.0 ac pounds per hour with retaining chain 2nd
alternate operating power rqmt
Output Voltage Rating:
12.0 dc volts 1st power output5.0 dc volts 2nd power output-5.0 dc volts 3rd power output-12.0 dc volts 4th power output
Input Frequency Rating:
47.0 hertz 1st alternate operating power rqmt and 440.0 hertz 1st alternate operating power rqmt47.0 hertz 2nd alternate operating power
rqmt and 440.0 hertz 2nd alternate operating power rqmt
Features Provided:
Over current protector and over temperature protection
Output Current Rating:
2.0 dc amperes 1st power output30.0 dc amperes 2nd power output0.4 dc amperes 3rd power output2.0 dc amperes 4th power output
Ripple Voltage At Full Load:
50.0 millivolts peak 1st power output100.0 millivolts peak 2nd power output50.0 millivolts peak 3rd power output50.0 millivolts peak 4th
power output
Output Connection Quantity:
2 1st power output2 2nd power output2 3rd power output2 4th power output
Output Connection Type:
Connector, receptacle 1st power outputconnector, receptacle 2nd power outputconnector, receptacle 3rd power outputconnector,
receptacle 4th power output
Input Current Rating:
3.0 ac amperes 1st alternate operating power rqmt1.5 ac amperes 2nd alternate operating power rqmt
Special Features:
Input/output connector: cannon plug p/n dcmm37pf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

No

V 20000