

View Online at <https://aerobasegroup.com/nsn/6130-01-372-7400>

**Overall Length:**

19.750 inches

**Overall Height:**

7.000 inches

**Overall Width:**

17.000 inches

**End Application:**

Multi-purpose

**Input Voltage Rating:**

100.0 ac pounds per hour dry 1st alternate operating power rqmt and 120.0 ac pounds per hour with retaining chain 1st alternate operating power rqmt

**Output Voltage Rating:**

120.0 ac volts multiple power outputs w/identical ratings

**Operating Ambient Temperature Range:**

-0.1/+40.0 degrees celsius

**Features Provided:**

Indicator light and on-off switch-indicator

**Output Current Rating:**

12.5 ac volt-ampere multiple power outputs w/identical ratings

**Output Phase:**

Single multiple power outputs w/identical ratings

**Output Connection Quantity:**

4 multiple power outputs w/identical ratings

**Output Connection Type:**

Receptacle, electrical multiple power outputs w/identical ratings

**Input Current Rating:**

11.0 ac amperes 2nd alternate operating power rqmt

**Battery Feature And Type:**

Rechargeable lead acid cell

**Battery Location:**

External

**Ventilation Design Type:**

Single fan

**Battery Switching Time:**

Instantaneous

**Battery Power Supply Emergency Operating Time:**

10.0

**Special Features:**

Between the ups 1500tr has input power cord/detachable with 5-15p plug; and four 5-15r output receptacles; battery p/n: b15tr sealed lead acid battery; a test/alarm disable switch located on the rear panel-test batteries during normal mode operation and disables the audible alarm when ups is running from battery reserve. Single power switch controls both input/output power to ups; and indicators (led) give ups status constantly; electrical power source relationship: operating; input phase: single; input frequency rating: 47.0 hz and 63.0 hz ; output frequency rating: 60.0 hz ; power supply output voltage rating: 120.0 volts multiple power outputs w/identical ratings

**Shelf Life:**

N/a

**Demilitarization:**

No

**Fig:**

A39900