NSN 6130-01-422-7681

Power Supply - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6130-01-422-7681

Overall Length: 16.500 inches End Application: An/mps-39 Input Voltage Rating: 105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqm Output Voltage Rating: 14.25 dc volts single power output and 15.75 dc volts single power output Input Frequency Rating: 47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A39900	
End Application: An/mps-39 Input Voltage Rating: 105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqm Output Voltage Rating: 14.25 dc volts single power output and 15.75 dc volts single power output Input Frequency Rating: 47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Overall Length:
An/mps-39 Input Voltage Rating: 105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqm Output Voltage Rating: 14.25 dc volts single power output and 15.75 dc volts single power output Input Frequency Rating: 47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	16.500 inches
Input Voltage Rating: 105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqm Output Voltage Rating: 14.25 dc volts single power output and 15.75 dc volts single power output Input Frequency Rating: 47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	End Application:
105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqm Output Voltage Rating: 14.25 dc volts single power output and 15.75 dc volts single power output Input Frequency Rating: 47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	An/mps-39
Output Voltage Rating: 14.25 dc volts single power output and 15.75 dc volts single power output Input Frequency Rating: 47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Input Voltage Rating:
14.25 dc volts single power output and 15.75 dc volts single power output Input Frequency Rating: 47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	105.0 ac pounds per hour dry single operating power rqmt and 132.0 ac pounds per hour with retaining chain single operating power rqm
Input Frequency Rating: 47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Output Voltage Rating:
47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	14.25 dc volts single power output and 15.75 dc volts single power output
Features Provided: Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Input Frequency Rating:
Over voltage protector and remote error sensing capability and voltage adjustment Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt
Output Current Rating: 41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Features Provided:
41.0 dc amperes single power output and 65.0 dc amperes single power output Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Over voltage protector and remote error sensing capability and voltage adjustment
Special Features: Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Output Current Rating:
Fungus proofing; convection cooled Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	41.0 dc amperes single power output and 65.0 dc amperes single power output
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
N/a Unit Of Measure: Demilitarization: No Fiig:	Fungus proofing; convection cooled
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A39900	Fiig:
	A39900