

View Online at <https://aerobasegroup.com/nsn/6130-01-462-4226>

Overall Length:

14.500 inches

Overall Height:

6.600 inches

Overall Width:

4.700 inches

Maximum Operating Altitude Rating:

10000.0 feet

Electrical Power Source Relationship:

Operating

Installation Design:

Cabinet with complete hardware

Input Phase:

Single single operating power rqmt

Input Voltage Rating:

120.0 ac pounds per hour wet single operating power rqmt

Output Voltage Rating:

115.0 ac volts single power output

Input Frequency Rating:

47.5 hertz single operating power rqmt and 63.0 hertz single operating power rqmt

Output Frequency Rating:

49.9 hertz single power output and 60.1 hertz single power output

Operating Ambient Temperature Range:

+32.0/+104.0 degrees fahrenheit

Output Control Quantity:

2 single power output

Output Control Type:

Voltage range single power output

Output Wattage Rating:

410.0 watts single power output

Features Provided:

Battery charger and circuit breaker and current regulator circuit and emi filter and indicator light and over voltage protector and programmable

Output Current Rating:

650.0 ac volt-ampere single power output

Output Phase:

Single single power output

Power Supply Output Current/voltage Characteristics:

Limiting voltage single power output

Output Connection Quantity:

6 single power output

Output Connection Type:

Receptacle, electrical single power output

Input Connection Type:

Connector, plug single operating power rqmt

Input Connection Quantity:

2 single operating power rqmt

Battery Feature And Type:

Rechargeable lead acid cell

Battery Recovery Time:

180.0

Program Compatibility:

Apple, ibm compatible or unix personal computers

Battery Switching Time:

Two milliseconds

Battery Power Supply Emergency Operating Time:

6.0

Power Supplies Programmed Per System:

2

Special Features:

Programming to automatically increase output up to 30 percent when input falls between 81 vac to 106 vac; automatically decreases output up to 15 percent when input is between 127 vac and 143 vac; overload protection on battery-internal current limiting and on line circuit breaker; modem/10 base-t/100 base-tx network cable port using single line (2 wire, rj11) or network (utp, rj45) compatible jacks; battery is user replaceable, hot swappable, sealed, and maintenance free; 14 day auto self test of all internal components; leds indicate when on line, on battery, ups overload, and replace battery; alarms for on battery, low battery, and ups overload; data saving unattended shutdown, advanced power management and diagnostic software included; db 9 serial interface port; output voltage on battery is stepped approximation to sine wave output at 115 vac plus or minus 8 percent

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A39900