

View Online at <https://aerobasegroup.com/nsn/6130-01-469-7380>

Overall Length:

4.870 inches

Overall Height:

2.070 inches

Overall Width:

4.000 inches

Electrical Power Source Relationship:

Operating

Input Voltage Rating:

103.5 ac pounds per hour dry single operating power rqmt and 253.0 ac pounds per hour with retaining chain single operating power rqmt

Output Voltage Rating:

24.0 dc volts single power output

Input Frequency Rating:

47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt

Operating Ambient Temperature Range:

+0.1/+50.0 degrees celsius

Features Provided:

Circuit overload protection device and voltage adjustment

Output Current Rating:

1.2 dc amperes single power output

Output Connection Quantity:

2 single power output

Ventilation Design Type:

Convection

Special Features:

Ouput current derated 10.0 percent for 50 hz operation; dc output adjustment range plus or minus 5.0 percent ; output ripple 0.02 percent peak to peak, 0.01 percent rms ; foldback current limit with automatic recovery; stability, plus or minus 0.3 percent for 24 hours after warmup; temperature rating is derated linearly from full rated at 50 degrees c to 40.0 percent at 70 degrees c; vibration resistant per mil-std-810b, method 514, procedure 1, curve ab (to 50 hz); shock resistant per mil-std-810b, method 516, procedure v; ic regulated design; 2 hour burn-in; moving air or conduction cooling recommended if in confined area

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A39900