

View Online at <https://aerobasegroup.com/nsn/6130-01-469-7380>

**Overall Length:**

4.870 inches

**Overall Height:**

2.070 inches

**Overall Width:**

4.000 inches

**Electrical Power Source Relationship:**

Operating

**Input Voltage Rating:**

103.5 ac pounds per hour dry single operating power rqmt and 253.0 ac pounds per hour with retaining chain single operating power rqmt

**Output Voltage Rating:**

24.0 dc volts single power output

**Input Frequency Rating:**

47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt

**Operating Ambient Temperature Range:**

+0.1/+50.0 degrees celsius

**Features Provided:**

Circuit overload protection device and voltage adjustment

**Output Current Rating:**

1.2 dc amperes single power output

**Output Connection Quantity:**

2 single power output

**Ventilation Design Type:**

Convection

**Special Features:**

Ouput current derated 10.0 percent for 50 hz operation; dc output adjustment range plus or minus 5.0 percent ; output ripple 0.02 percent peak to peak, 0.01 percent rms ; foldback current limit with automatic recovery; stability, plus or minus 0.3 percent for 24 hours after warmup; temperature rating is derated linearly from full rated at 50 degrees c to 40.0 percent at 70 degrees c; vibration resistant per mil-std-810b, method 514, procedure 1, curve ab (to 50 hz); shock resistant per mil-std-810b, method 516, procedure v; ic regulated design; 2 hour burn-in; moving air or conduction cooling recommended if in confined area

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A39900