

View Online at <https://aerobasegroup.com/nsn/6130-01-491-4273>

Overall Length:

6.000 inches

Overall Height:

8.800 inches

Overall Width:

3.280 inches

End Application:

Mk13mod4, launching system guided missile

Input Phase:

Single single operating power rqmt

Input Voltage Rating:

105.0 ac volts single operating power rqmt and 130.0 ac volts single operating power rqmt

Output Voltage Rating:

5.0 dc volts single power output

Input Frequency Rating:

47.0 hertz single operating power rqmt and 500.0 hertz single operating power rqmt

Operating Ambient Temperature Range:

-20.0/+71.0 degrees celsius

Features Provided:

Emi filter

Output Current Rating:

17.0 dc amperes single power output

Ripple Voltage At Full Load:

25.0 millivolts average single power output

Output Connection Type:

Screw single power output and terminal strip single power output

Special Features:

Storage temp minus 20degc to 85degc; shock and vibration unit shall be capable of meeting mil-s-9010 grade a type a class i and mil-std-167-1 ty i when installed in next higher assembly; voltage output terminals - 10-32unc screws with ring type terminal strips; finish coat exposed metallic parts with corrosion protective coating; isolation: output shall be floated up to 200vdc above or below ground potential; input power is 105 to 130vdc, 47 to 500hz, single phase or 105 to 184vdc with terminal 1 positive

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A39900