

View Online at <https://aerobasegroup.com/nsn/6130-01-501-9107>

**Overall Length:**

21.000 inches

**Overall Height:**

7.000 inches

**Overall Width:**

17.000 inches

**Environmental Protection:**

Rain tight and moisture proof and shock proof and magnetic shield

**Battery Quantity:**

2

**End Application:**

7253800 (34228), phot mast, bay 9

**Maximum Operating Altitude Rating:**

15000.0 feet

**Electrical Power Source Relationship:**

Operating and self-contained

**Input Phase:**

Three single operating power rqmt

**Input Voltage Rating:**

80.0 ac pounds per hour dry single operating power rqmt and 265.0 ac pounds per hour with retaining chain single operating power rqmt

**Output Voltage Rating:**

2500.0 ac volts single power output

**Input Frequency Rating:**

47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt

**Output Frequency Rating:**

60.0 hertz single power output

**Operating Ambient Temperature Range:**

-18.0/+50.0 degrees celsius

**Output Control Quantity:**

1 single power output

**Output Control Type:**

Switch single power output

**Output Wattage Rating:**

2.0 kilowatts single power output

**Features Provided:**

Auto parallel operating and power to output indicator light and battery charger and emi filter and ground wire terminal and indicator light and on-off switch-indicator

**Output Current Rating:**

44.0 ac amperes single power output

**Output Phase:**

Single single power output

**Output Control Location:**

Front panel single power output

**Output Connection Quantity:**

1 1st power output

**Output Connection Type:**

Connector, plug single power output

**Battery Feature And Type:**

Rechargeable lead acid cell

**Battery Location:**

Internal

**Ventilation Design Type:**

Louvers and single fan

**Battery Recovery Time:**

240.0

**Product Name:**

Rugged-ups 2500

**Battery Power Supply Emergency Operating Time:**

30.0

**Special Features:**

7extended run input; can only be used in parallel operation; includes external battery connector, a 9-pin d-type female communication port connector compatible with rs-232- and an auxiliary port d-type 25-pin female connector for parallel operation

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A39900