NSN 6130-01-501-9107

Power Supply - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-01-501-9107

Overall Length:

21.000 inches

Overall Height:

7.000 inches

Overall Width:

17.000 inches

Environmental Protection:

Rain tight and moisture proof and shock proof and magnetic shield

Battery Quantity:

2

End Application:

7253800 (34228), phot mast, bay 9

Maximum Operating Altitude Rating:

15000.0 feet

Electrical Power Source Relationship:

Operating and self-contained

Input Phase:

Three single operating power rqmt

Input Voltage Rating:

80.0 ac pounds per hour dry single operating power rqmt and 265.0 ac pounds per hour with retaining chain single operating power rqmt

Output Voltage Rating:

2500.0 ac volts single power output

Input Frequency Rating:

47.0 hertz single operating power rqmt and 440.0 hertz single operating power rqmt

Output Frequency Rating:

60.0 hertz single power output

Operating Ambient Tempurature Range:

-18.0/+50.0 degrees celsius

Output Control Quantity:

1 single power output

Output Control Type:

Switch single power output

Output Wattage Rating:

2.0 kilowatts single power output

Features Provided:

Auto parallel operating and power to output indicator light and battery charger and emi filter and ground wire terminal and indicator light and on-off switch-indicator

Output Current Rating:

44.0 ac amperes single power output

Output Phase:

Single single power output

Output Control Location:

Front panel single power output

NSN 6130-01-501-9107

Power Supply - Page 2 of 2



Output Connection Quantity:

1 1st power output

Output Connection Type:

Connector, plug single power output

Battery Feature And Type:

Rechargeable lead acid cell

Battery Location:

Internal

Ventilation Design Type:

Louvers and single fan

Battery Recovery Time:

240.0

Product Name:

Rugged-ups 2500

Battery Power Supply Emergency Operating Time:

30.0

Special Features:

7extended run input; can only be used in parallel operation; includes external battery connector, a 9-pin d-type female communication port connector compatible with rs-232- and an auxiliary port d-type 25-pin female connector for parallel operation

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A39900