Power Supply - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6130-01-502-6352

Overall Length: 6.500 inches **Overall Height:** 2.400 inches **Overall Width:** 6.700 inches **End Application:** P3 orion **Maximum Operating Altitude Rating:** 55000.0 feet Installation Design: Rack Input Voltage Rating: 20.0 dc volts single operating power rgmt and 40.0 dc volts single operating power rgmt **Output Voltage Rating:** 0.0 dc volts single power output and 28.0 dc volts single power output **Operating Ambient Tempurature Range:** -55.0/+71.0 degrees celsius **Output Wattage Rating:** 300.0 watts single power output **Ripple Voltage At Full Load:** 25.0 millivolts peak single power output **Product Name:** Converter, regulator **Special Features:**

Functional description a pulse width modulated dc to dc converter that provided regulated multiple output power; converts transforms an unregulated 28 vdc to a regulated adjustable dc output via a remote control potentiometer or voltage for voltage controlled models; primarily designed to control the light intensity of incandescent bulbs in lighting systems; input voltage 28 vdc; output voltage adjustable with external 5k ohm, 1/2 w rheostat or voltage 0-5 v dc; regulation 2 pct for line, 2 pct load and 2.5 pct temperature; common mode isolation 40 db; output ripple 25mv p-p or less; protection overvoltage output voltage is limited to aproximately 125 pct of rating even though remote control rheostat opens or internal failure occurs; output current 11 adc total; efficiency 84

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A39900