

View Online at <https://aerobasegroup.com/nsn/6130-01-528-0404>

**Overall Length:**

23.500 inches

**Overall Height:**

5.250 inches

**Overall Width:**

19.000 inches

**Environmental Protection:**

Shock proof

**Major Components:**

Ups connectors, cable connectors, pinouts, ext.Battery, remote control receptacle & mating plug, status plug, 6 nema 5-15p output receptacles, mounting options

**Battery Quantity:**

1

**End Application:**

POWE-RS-TAT-IONU

**Maximum Operating Altitude Rating:**

10000.0 feet

**Input Phase:**

Single single operating power rqmt and two single operating power rqmt and three single operating power rqmt

**Frequency Regulation Percent:**

1.0 multiple power outputs w/identical ratings

**Input Voltage Rating:**

115.0 ac pounds per hour wet single operating power rqmt

**Output Voltage Rating:**

120.0 ac volts multiple power outputs w/identical ratings and 600.0 ac volts multiple power outputs w/identical ratings

**Input Frequency Rating:**

46.0 hertz single operating power rqmt and 70.0 hertz single operating power rqmt

**Output Frequency Rating:**

50.0 hertz multiple power outputs w/identical ratings and 60.0 hertz multiple power outputs w/identical ratings

**Operating Ambient Temperature Range:**

+32.0/+126.0 degrees fahrenheit

**Output Control Quantity:**

8 multiple power outputs w/identical ratings

**Output Control Type:**

Switch multiple power outputs w/identical ratings

**Features Provided:**

Circuit overload protection device and filter and fuse and grounding and battery check switch and function switch and remote control

**Output Current Rating:**

1000.0 ac volt-ampere multiple power outputs w/identical ratings

**Output Phase:**

Single multiple power outputs w/identical ratings and two multiple power outputs w/identical ratings and three multiple power outputs w/identical ratings

**Output Waveform And Current Type:**

Full wave rectified sine wave ac multiple power outputs w/identical ratings and half wave rectified sine wave ac multiple power outputs w/identical ratings

**Power Supply Output Current/voltage Characteristics:**

Constant voltage multiple power outputs w/identical ratings and limiting voltage multiple power outputs w/identical ratings

**Output Control Location:**

Front panel multiple power outputs w/identical ratings and rear panel multiple power outputs w/identical ratings

**Output Connection Quantity:**

8 multiple power outputs w/identical ratings

**Output Connection Type:**

Connector, receptacle multiple power outputs w/identical ratings and pin plug multiple power outputs w/identical ratings

**Input Current Rating:**

12.0 ac amperes 1st operating power rqmt

**Input Connection Type:**

Pin plug single operating power rqmt

**Input Connection Quantity:**

8 single operating power rqmt

**Battery Location:**

External

**Ventilation Design Type:**

Air cooled

**Battery Recovery Time:**

480.0

**Program Compatibility:**

ieee587 & ul1449; unix, hp-ux, novell netware & windows nt

**Product Name:**

Ups 1.0 kva

**Battery Power Supply Emergency Operating Time:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A39900