

View Online at <https://aerobasegroup.com/nsn/6130-01-528-0404>

Overall Length:

23.500 inches

Overall Height:

5.250 inches

Overall Width:

19.000 inches

Environmental Protection:

Shock proof

Major Components:

Ups connectors, cable connectors, pinouts, ext.Battery, remote control receptacle & mating plug, status plug, 6 nema 5-15p ouput receptacles, mounting options

Battery Quantity:

1

End Application:

POWE-RS-TAT-IONU

Maximum Operating Altitude Rating:

10000.0 feet

Input Phase:

Single single operating power rqmt and two single operating power rqmt and three single operating power rqmt

Frequency Regulation Percent:

1.0 multiple power outputs w/identical ratings

Input Voltage Rating:

115.0 ac pounds per hour wet single operating power rqmt

Output Voltage Rating:

120.0 ac volts multiple power outputs w/identical ratings and 600.0 ac volts multiple power outputs w/identical ratings

Input Frequency Rating:

46.0 hertz single operating power rqmt and 70.0 hertz single operating power rqmt

Output Frequency Rating:

50.0 hertz multiple power outputs w/identical ratings and 60.0 hertz multiple power outputs w/identical ratings

Operating Ambient Tempurature Range:

+32.0/+126.0 degrees fahrenheit

Output Control Quantity:

8 multiple power outputs w/identical ratings

Output Control Type:

Switch multiple power outputs w/identical ratings

Features Provided:

Circuit overload protection device and filter and fuse and grounding and battery check switch and function switch and remote control

Output Current Rating:

1000.0 ac volt-ampere multiple power outputs w/identical ratings

Output Phase:

Single multiple power outputs w/identical ratings and two multiple power outputs w/identical ratings and three multiple power outputs w/identical ratings

Output Waveform And Current Type:

Full wave rectified sine wave ac multiple power outputs w/identical ratings and half wave rectified sine wave ac multiple power outputs w/identical ratings

Power Supply Output Current/voltage Characteristics:

Constant voltage multiple power outputs w/identical ratings and limiting voltage multiple power outputs w/identical ratings

Output Control Location:

Front panel multiple power outputs w/identical ratings and rear panel multiple power outputs w/identical ratings

Output Connection Quantity:

8 multiple power outputs w/identical ratings

Output Connection Type:

Connector, receptacle multiple power outputs w/identical ratings and pin plug multiple power outputs w/identical ratings

Input Current Rating:

12.0 ac amperes 1st operating power rqmt

Input Connection Type:

Pin plug single operating power rqmt

Input Connection Quantity:

8 single operating power rqmt

Battery Location:

External

Ventilation Design Type:

Air cooled

Battery Recovery Time:

480.0

Program Compatibility:

ieee587 & ul1449; unix, hp-ux, novell netware & windows nt

Product Name:

Ups 1.0 kva

Battery Power Supply Emergency Operating Time:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A39900