NSN 6130-01-565-7580

Power Supply - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6130-01-565-7580

Overall Length:

26.000 inches

Overall Height:

5.100 inches

Overall Width:

17.000 inches

Input Frequency Rating:

50.0 hertz single operating power rqmt and 60.0 hertz single operating power rqmt

Output Frequency Rating:

50.0 hertz single power output and 60.0 hertz single power output

Operating Ambient Tempurature Range:

+32.0/+104.0 degrees fahrenheit

Output Wattage Rating:

4200.0 watts single power output

Product Name:

Apc smart ups rt 6000va rm 208v

Battery Power Supply Emergency Operating Time:

5.3

Special Features:

Includes cd with software, rack mounting support rails, smart ups signalling rs-232 cable, user manual; output power capacity and maximum configurable power 4200 watts / 6000 va; output voltage 208 v; output voltage note configurable for 208 or 240 output voltage; efficienty at full load 92.00 pct; output voltage distortion less than 3 pct; output frequency, sync to mains, 50/60 hz porm 3 hz user adjustable porm 0.1; crest factor 3: 1; waveform type sine wave; output connections nema l6-20r, 2 and nema l6-30r, 2; input bypass internal bypass, automatic and manual; cord length 10 feet; input voltage 160-280 v; input voltage adjustable for mains operation 100-280 v; other input voltages 240; battery type maintenance free sealed lead-acid battery with suspended electrolyte, leakproof; included battery modules 2; typical recharge time 2.5 hrs; replacement battery rbc44; rbcquantity type 1; typical back up time at half load 15.8 min, 2100 watts

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A39900