

View Online at <https://aerobasegroup.com/nsn/6130-01-575-0130>

**Overall Length:**

19.500 inches

**Overall Height:**

10.250 inches

**Overall Width:**

9.000 inches

**Environmental Protection:**

Magnetic shield and dripproof

**Major Components:**

On-line double-conversion ups tower system; simultaneous communications via hid-compliant usb port, serial port and snmp/web slot card; fault-tolerant auto-bypass

**Battery Quantity:**

1

**End Application:**

Mission-critical applications

**Output Impedance Rating:**

9.0 ohms single power output

**Frequency Regulation Percent:**

2.0 single power output

**Input Voltage Rating:**

110.0 dc volts single operating power rqmt and 120.0 dc volts single operating power rqmt

**Output Voltage Rating:**

110.0 ac volts single power output and 120.0 ac volts single power output

**Input Frequency Rating:**

50.0 hertz single operating power rqmt and 60.0 hertz single operating power rqmt

**Output Frequency Rating:**

50.0 hertz single power output and 60.0 hertz single power output

**Load Type:**

Resistive single power output

**Output Control Quantity:**

1 single power output

**Output Control Type:**

Voltage range single power output

**Output Wattage Rating:**

1600.0 watts single power output

**Features Provided:**

Reverse voltage protection and remote error sensing capability

**Output Current Rating:**

2200.0 ac amperes single power output

**Output Phase:**

Single single power output

**Output Waveform And Current Type:**

Full wave rectified sine wave ac single power output

**Power Supply Output Current/voltage Characteristics:**

Constant current single power output and constant voltage single power output

**Output Control Location:**

Front panel single power output

**Output Connection Quantity:**

7 single power output

**Output Connection Type:**

Solder lug single power output

**Input Current Rating:**

16.0 dc amperes single operating power rqmt and 17.6 dc amperes single operating power rqmt

**Input Connection Type:**

Connector, plug single operating power rqmt

**Input Connection Quantity:**

1 single operating power rqmt

**Battery Feature And Type:**

Iso precision class 10 head outside diameter

**Battery Location:**

External

**Ventilation Design Type:**

Single fan

**Warm Up Time In Minutes:**

0

**Battery Recovery Time:**

5.0

**Program Compatibility:**

Watchdog compatibility

**Power Supply Efficiency Line:**

99.0

**Power Supply Efficiency Battery:**

99.0

**Product Name:**

Ups system tower

**Battery Power Supply Emergency Operating Time:**

4.5 and 14.0

**Special Features:**

Black smart online expandable tower ups system

**Special Test Features:**

Tested to ul177 (usa), csa(canada), nom(mexico), class a(emissions) fcc part 68/industry canada, rohs compliant

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A39900