

View Online at <https://aerobasegroup.com/nsn/6130-01-575-0130>

Overall Length:

19.500 inches

Overall Height:

10.250 inches

Overall Width:

9.000 inches

Environmental Protection:

Magnetic shield and dripproof

Major Components:

On-line double-conversion ups tower system; simultaneous communications via hid-compliant usb port, serial port and snmp/web slot card; fault-tolerant auto-bypass

Battery Quantity:

1

End Application:

Mission-critical applications

Output Impedance Rating:

9.0 ohms single power output

Frequency Regulation Percent:

2.0 single power output

Input Voltage Rating:

110.0 dc volts single operating power rqmt and 120.0 dc volts single operating power rqmt

Output Voltage Rating:

110.0 ac volts single power output and 120.0 ac volts single power output

Input Frequency Rating:

50.0 hertz single operating power rqmt and 60.0 hertz single operating power rqmt

Output Frequency Rating:

50.0 hertz single power output and 60.0 hertz single power output

Load Type:

Resistive single power output

Output Control Quantity:

1 single power output

Output Control Type:

Voltage range single power output

Output Wattage Rating:

1600.0 watts single power output

Features Provided:

Reverse voltage protection and remote error sensing capability

Output Current Rating:

2200.0 ac amperes single power output

Output Phase:

Single single power output

Output Waveform And Current Type:

Full wave rectified sine wave ac single power output

Power Supply Output Current/voltage Characteristics:

Constant current single power output and constant voltage single power output

Output Control Location:

Front panel single power output

Output Connection Quantity:

7 single power output

Output Connection Type:

Solder lug single power output

Input Current Rating:

16.0 dc amperes single operating power rqmt and 17.6 dc amperes single operating power rqmt

Input Connection Type:

Connector, plug single operating power rqmt

Input Connection Quantity:

1 single operating power rqmt

Battery Feature And Type:

Iso precision class 10 head outside diameter

Battery Location:

External

Ventilation Design Type:

Single fan

Warm Up Time In Minutes:

0

Battery Recovery Time:

5.0

Program Compatibility:

Watchdog compatibility

Power Supply Efficiency Line:

99.0

Power Supply Efficiency Battery:

99.0

Product Name:

Ups system tower

Battery Power Supply Emergency Operating Time:

4.5 and 14.0

Special Features:

Black smart online expandable tower ups system

Special Test Features:

Tested to ul177 (usa), csa(canada), nom(mexico), class a(emissions) fcc part 68/industry canada, rohs compliant

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A39900