

View Online at <https://aerobasegroup.com/nsn/6130-01-579-3661>

**Overall Length:**

390.0 millimeters

**Overall Height:**

317.0 millimeters

**Overall Width:**

80.0 millimeters

**End Application:**

Tiger dimulator helicopter; stss hap/e and had/e

**Input Voltage Rating:**

184.0 ac volts single operating power rqmt and 264.0 ac volts single operating power rqmt

**Output Voltage Rating:**

230.0 ac volts single power output

**Input Frequency Rating:**

50.0 hertz single operating power rqmt and 60.0 hertz single operating power rqmt

**Output Frequency Rating:**

50.0 hertz single power output and 60.0 hertz single power output

**Output Control Type:**

Voltage adjustment single power output

**Output Wattage Rating:**

600.0 watts single power output

**Features Provided:**

Voltage adjustment and over voltage protector

**Output Current Rating:**

1500.0 ac volt-ampere single power output

**Output Phase:**

Single single power output or three single power output

**Power Supply Output Current/voltage Characteristics:**

Constant current single power output and constant voltage single power output

**Output Connection Quantity:**

9 single power output

**Output Connection Type:**

Connector, receptacle single power output

**Battery Feature And Type:**

Rechargeable lead acid cell

**Battery Location:**

Internal

**Product Name:**

Uninterruptible power supply

**Battery Switching Time:**

Instantaneous

**Battery Power Supply Emergency Operating Time:**

4.0

**Special Features:**

Battery charger operates when the ups is under power; replacment indicators are led and audible alarm; combined usb and serial port; 4/1 sockets with surge protection and backup/sockets with surge protect for peripherals; 5 multi way sockets-french sockets; adjustable voltage and settable voltage

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A39900