

View Online at <https://aerobasegroup.com/nsn/6130-01-579-3661>

Overall Length:

390.0 millimeters

Overall Height:

317.0 millimeters

Overall Width:

80.0 millimeters

End Application:

Tiger dimulator helicopter; stss hap/e and had/e

Input Voltage Rating:

184.0 ac volts single operating power rqmt and 264.0 ac volts single operating power rqmt

Output Voltage Rating:

230.0 ac volts single power output

Input Frequency Rating:

50.0 hertz single operating power rqmt and 60.0 hertz single operating power rqmt

Output Frequency Rating:

50.0 hertz single power output and 60.0 hertz single power output

Output Control Type:

Voltage adjustment single power output

Output Wattage Rating:

600.0 watts single power output

Features Provided:

Voltage adjustment and over voltage protector

Output Current Rating:

1500.0 ac volt-ampere single power output

Output Phase:

Single single power output or three single power output

Power Supply Output Current/voltage Characteristics:

Constant current single power output and constant voltage single power output

Output Connection Quantity:

9 single power output

Output Connection Type:

Connector, receptacle single power output

Battery Feature And Type:

Rechargeable lead acid cell

Battery Location:

Internal

Product Name:

Uninterruptible power supply

Battery Switching Time:

Instantaneous

Battery Power Supply Emergency Operating Time:

4.0

Special Features:

Battery charger operates when the ups is under power; replacment indicators are led and audible alarm; combined usb and serial port; 4/1 sockets with surge protection and backup/sockets with surge protect for peripherals; 5 multi way sockets-french sockets; adjustable voltage and settable voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A39900