NSN 6130-01-587-6916

Uninterruptible Power Supply - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6130-01-587-6916

In	nut	V٥	Itage	Rat	ina:
	vul	v	ıtauc	: IXai	ши.

120.0 ac volts single operating power rqmt

Output Voltage Rating:

120.0 ac volts multiple power outputs w/identical ratings

Output Frequency Rating:

60.0 hertz multiple power outputs w/identical ratings

Output Wattage Rating:

700.0 watts multiple power outputs w/identical ratings

Output Current Rating:

1000.0 ac volt-ampere multiple power outputs w/identical ratings

Output Waveform And Current Type:

Sinusoidal ac multiple power outputs w/identical ratings

Battery Location:

Internal

Ventilation Design Type:

Single fan

Product Name:

1000va, rackmount 2 unit, 120v

Special Features:

Output kva capacity: 1; output power factor: 0.7; output voltage regulation (line mode) minus 21 percent, plus 8 percent; built-in ups output receptacles: 6 5-15r outlets; ; output voltage regulation (battery mode) plus or minus 5 percent; built-in controllable switched load banks: two switchable two-outlet 5-15r load banks; rated input current (at load) 6.8a; ups input connection type: 5-15p; input circuit breaker: 15a; ups input cord length: 3 m; recommended electrical service: 15a 120v; battery: full load runtime: 7 minutes (700w), half load runtime: 17 minutes (350w), dc system voltage: 24 dc, battery recharge rate: less than 4 hours from 10 percent to 90 percent

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A39900