NSN 6130-01-623-3229

Uninterruptible Power Supply - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-01-623-3229

559.0 millimeters

Overall Height:

95.0 millimeters

Overall Width:

432.0 millimeters

Overall Length:

Battery Quantity:

1

End Application:

An/ffc- (v) 2 com sys light signal

Maximum Operating Altitude Rating:

3000.0 meters

Input Voltage Rating:

120.0 ac volts single operating power rqmt

Output Voltage Rating:

120.0 ac volts single power output

Input Frequency Rating:

50.0 hertz and 60.0 hertz single operating power rqmt

Output Frequency Rating:

50.0 hertz and 60.0 hertz single power output

Operating Ambient Tempurature Range:

+0.0 to 40.0 degrees celsius

Output Wattage Rating:

1050.0 watts single power output

Output Current Rating:

1500.0 ac volt-ampere single power output

Output Connection Quantity:

6 single power output

Output Connection Type:

Connector, receptacle single power output

Input Current Rating:

1500.0 ac amperes single operating power rqmt

Input Connection Type:

Connector, plug single operating power rqmt

Input Connection Quantity:

1 single operating power rqmt

Battery Feature And Type:

Rechargeable lead acid cell

Battery Location:

Internal

Battery Recovery Time:

3.0

NSN 6130-01-623-3229

Uninterruptible Power Supply - Page 2 of 2



М	roc	iuct	Name:	

Apc smart-ups rt 1500va rack tower 120v

Special Features:

Interface port db-9 rs-232, smart-slot, usb, extended runtime model, ra ch height 2u

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A39900