NSN 6130-01-633-6144

Uninterruptible Power Supply - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6130-01-633-6144

Overall Length:

20.000 inches

Overall Height:

3.450 inches

Overall Width:

19.000 inches

End Application:

Sb-010312-a (12763), ivn switch cabinet

Maximum Operating Altitude Rating:

10000.0 feet

Input Phase:

Three single operating power rgmt

Frequency Regulation Percent:

0.25 single power output

Input Voltage Rating:

115.0 ac volts and 230.0 ac volts single operating power rqmt

Output Voltage Rating:

120.0 ac volts single power output

Input Frequency Rating:

50.0 hertz and 60.0 hertz single operating power rqmt

Output Frequency Rating:

50.0 hertz and 60.0 hertz single power output

Operating Ambient Tempurature Range:

+0.0 to 50.0 degrees celsius

Output Current Rating:

10.4 ac amperes and 20.8 ac amperes single power output

Output Phase:

Three single power output

Output Connection Quantity:

2 single power output

Output Connection Type:

Connector, receptacle single power output

Input Current Rating:

8.8 ac amperes and 25.0 ac amperes single operating power rqmt

Input Connection Type:

Connector, plug single operating power rqmt

Input Connection Quantity:

1 single operating power rqmt

Power Supply Efficiency Line:

0.85

Product Name:

2.5kva ups; continuous power system, 2500 va

NSN 6130-01-633-6144

Uninterruptible Power Supply - Page 2 of 2



Battery Power Supply Emergency Operating Time:

13.0 and 36.0

Special Features:

Ups protection: input and output short circuit; input and output overload; excessive battery discharge: intelligent computer interface; sequenced led indicators: battery level, load level; single indicators: ac in ok, inverter on, battery on, bypass on, cold start, ac out, fault, replace battery; audible alarms: utility interrupt, ups on, overload, low battery

c	ha	16	ı	ife:	
	ne	·IT		ITE:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A39900