## NSN 6135-01-641-8640

Nonrechargeable Battery - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6135-01-641-8640

Battery Electrolyte: Lithium  End Application: Wide area augmentation (waas)  Approximate Shelf Life: 10.00 years  Special Features: Wide area temp range: discharge -40 degrees c to 70 degrees; charge -10 degrees c to 60 degrees c; high energy density: by volume: 420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid; separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid  Shape: Rectangular  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	
End Application:  Wide area augmentation (waas)  Approximate Shelf Life:  10.00 years  Special Features:  Wide area temp range: discharge -40 degrees c to 70 degrees; charge -10 degrees c to 60 degrees c; high energy density: by volume:  420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid; separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid  Shape:  Rectangular  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Battery Electrolyte:
Wide area augmentation (waas)  Approximate Shelf Life:  10.00 years  Special Features:  Wide area temp range: discharge -40 degrees c to 70 degrees; charge -10 degrees c to 60 degrees c; high energy density: by volume:  420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid; separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid  Shape:  Rectangular  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	_ithium
Approximate Shelf Life:  10.00 years  Special Features:  Wide area temp range: discharge -40 degrees c to 70 degrees; charge -10 degrees c to 60 degrees c; high energy density: by volume:  420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid; separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid  Shape:  Rectangular  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	End Application:
Special Features: Wide area temp range: discharge -40 degrees c to 70 degrees; charge -10 degrees c to 60 degrees c; high energy density: by volume: 420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid; separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid Shape: Rectangular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Nide area augmentation (waas)
Special Features:  Wide area temp range: discharge -40 degrees c to 70 degrees; charge -10 degrees c to 60 degrees c; high energy density: by volume:  420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid; separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid  Shape:  Rectangular  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Approximate Shelf Life:
Wide area temp range: discharge -40 degrees c to 70 degrees; charge -10 degrees c to 60 degrees c; high energy density: by volume: 420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid; separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid  Shape: Rectangular  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	10.00 years
420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid; separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid  Shape: Rectangular Shelf Life: N/a Unit Of Measure: Demilitarization: No	Special Features:
separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser weld lid  Shape: Rectangular  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No	Nide area temp range: discharge -40 degrees c to 70 degrees; charge -10 degrees c to 60 degrees c; high energy density: by volume:
lid Shape: Rectangular Shelf Life: N/a Unit Of Measure: Demilitarization: No	420wh/l; by weight: 177wh/kg; fast charge with minimal loss of cycle life (80 percent capacity in 30 mins); safety features; patented cid;
Shape: Rectangular Shelf Life: N/a Unit Of Measure: Demilitarization: No	separator with integrated shutdown mechanism; redundant vents; aluminum can construction to optimize thermal dissipation; laser welded
Rectangular  Shelf Life: N/a Unit Of Measure: Demilitarization: No	id .
Shelf Life:  N/a Unit Of Measure: Demilitarization: No	Shape:
N/a Unit Of Measure: Demilitarization: No	Rectangular
Unit Of Measure: Demilitarization: No	Shelf Life:
Demilitarization:  No	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Filg:
T139-a	Г139-а