## NSN 6140-01-185-5462

Storage Battery - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6140-01-185-5462

Terminal Quantity:
2
Terminal Type:
Solder tab
Overall Length:
5.950 inches
Overall Height:
4.020 inches
Overall Width:
2.520 inches
Ventilation Design Type:
Venting accomplished through design
Case Material:
Plastic, polystyrene
Battery Electrolyte:
Silica-gel
Terminal Location:
Top at each end
Tap Voltage In Volts:
9.6 and 10.14 and 10.26 and 10.5
Ampere Hour Capacity:
Ampere Hour Capacity: 2.40 and 3.90 and 4.30 and 4.50
2.40 and 3.90 and 4.30 and 4.50
2.40 and 3.90 and 4.30 and 4.50 Time Capacity In Hours:
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity:
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature:
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included  Case Design Type:
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included  Case Design Type: Sealed
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included  Case Design Type: Sealed  Voltage In Volts:
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included  Case Design Type: Sealed  Voltage In Volts: 12.0
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included  Case Design Type: Sealed  Voltage In Volts: 12.0  Shelf Life:
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included  Case Design Type: Sealed  Voltage In Volts: 12.0  Shelf Life: N/a
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included  Case Design Type: Sealed  Voltage In Volts: 12.0  Shelf Life: N/a
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours:  1.00 and 5.00 and 10.00 and 20.00  Cell Quantity:  6  Nonspilling Feature: Included  Case Design Type: Sealed  Voltage In Volts:  12.0  Shelf Life: N/a  Unit Of Measure:
2.40 and 3.90 and 4.30 and 4.50  Time Capacity In Hours: 1.00 and 5.00 and 10.00 and 20.00  Cell Quantity: 6  Nonspilling Feature: Included  Case Design Type: Sealed  Voltage In Volts: 12.0  Shelf Life: N/a  Unit Of Measure: Demilitarization: