

View Online at <https://aerobasegroup.com/nsn/6140-01-477-8246>

**Terminal Quantity:**

2

**Terminal Type:**

Threaded stud

**Overall Length:**

10.250 inches

**Overall Height:**

8.125 inches

**Overall Width:**

6.750 inches

**Ventilation Design Type:**

Venting accomplished through design

**Separator Material:**

Glass and fiber

**Case Material:**

Plastic

**Fording Feature:**

Included

**Ampere Hour Capacity:**

50.00

**Time Capacity In Hours:**

20.00

**Cell Quantity:**

6

**Plate Material:**

Lead

**Plate Quantity Per Cell:**

2

**Nonspilling Feature:**

Included

**Charge Indicator:**

Not included

**Electrolyte Level Indicator:**

Not included

**Storage/shipment Condition:**

Wet charged

**Integral Charging Facility:**

Not included

**Case Design Type:**

Sealed

**Voltage In Volts:**

12.0

**Special Features:**

750 cold crank amps; wound cell element construction; polypropylene case/cover material; vitreous fiber separator material; 1.300 electrolyte specific gravity; sae side/bottom hold down config.; 3/8-16 pos., 5/16-18 neg. Stud terminals; 13.5 to 13.8 volts, 1 amp max. Trickle charging (float); 13.5 to 14.5 volts, 10 amps max. Normal charging; 15.0 volts max(14.6 to 14.8 is ideal) 60 amps max. Boost charging; charge until current is less than 1 amp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T139-a